



DIXION 6 Channel ECG ECG-1006

Portable and lightweight digital 6-channel ECG machine. Large graphic LCD screen with backlight. Simultaneous acquisition of 12 leads. ECG data storage (up to 200 records). Automatic ECG data interpretation. Built-in rechargeable lithium battery and thermal printer.

Features:

- 120s real-time ECG waveforms freezing and review to assist your diagnosis
- 5,7" high resolution antiglare color screen
- Anti-noise technology with comprehensive filters
- USB/RS232/Ethernet connection to PC data transmission
- "Stand by" regime for saving battery power
- Various report formats to meet different needs
- Screen image "pause" and "record" in chosen format
- Automatic arrhythmia detection and recording
- Compact and lightweight design with carry handle
- Accurate ECG Interpretation
- One-touch control
- Defibrillation protection

Specification:

*	
Features	Description
Lead	12 Standard leads
Input Circuit	Floating input circuit, protection from defibrillation and pace-maker
Acquisition mode	12 leads simultaneously
Frequency Response	$\pm 0.05 \text{ Hz} - 150 \text{ Hz}$
Input Impedance	$\geq 50 \text{ M}\Omega \text{ (10Hz)}$
Input Circuit Current	\leq 0.01 μ A
Noise level	$< 12.5 \mu Vp-p$
Anti Baseline Drift	Automatic
Filter	EMG-Filter : \pm 25Hz/ 35Hz/ 45Hz/ off DFT-Filter : \pm 0.05/ 0.15/ 0.25/ 0.32/ 0.5/ 0.67Hz Lowpass filter : \pm 150/ 100/ 75 Hz AC-Filter : On/Off
CMRR	$\geq 121 \text{ dB} / \geq 115 \text{ dB}$
Recording Mode	Auto/Manual
Safety Standards	IEC 60601-1:1988+A1:1991+A2:1995, EN 60601-1:1990+A1:1993+A2:1995, IEC 60601-1-2:2001+A1:2004, EN 60601-1-2:2001+A1:2006, ANSI/AAMI EC11, IEC/EN 60601-2-25, IEC/EN 60601-2-51
Power supply	AC: 100 - 240 V, 50 - 60 Hz Built-in rechargeable Li-ion battery: voltage 14.8 V
Record Paper	Folded thermal paper 110mm x 140mm, 150 pages
Paper speed	± 5; 6.25; 10; 12,5; 25; 50 mm/s
Dimension	310 x 322 x 101 mm
Display	3.5" single color LCD screen
Time constant	\geq 3,2 s
Communication Interface	Ethernet, RS 232, USB
Lead for rhythm test	1-lead Option
Weight	2.6kg

± = Tolerance Measurement 10%

Accessories:

- Adapter lead cable banana to clip
- Chest electrodes bulb
- Limb electrodes
- ECG Paper

Chest electrodes bulb



Adapter lead cable banana to clip



Limb electrodes



ECG paper

